

08-29-00

A

**UTILITY
PATENT APPLICATION
TRANSMITTAL**

Attorney Docket No.

1135.ACT2.PT

First Inventor or Application Identifier

Sovine

Title

CLEARING TRAP

Express Mail Label No.

EL593619398US

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

APPLICATION ELEMENTS and ACCOMPANYING APPLICATION PARTS

Enclosed for filing, please find the following items:

1. ☒ Specification [Total Pages 23]
2. ☒ Drawing(s) [Total Sheets 7]
☒ Informal ☐ Formal
3. ☐ Oath/Declaration, Power of Attorney, and Petition
 - a. ☐ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d)) (for continuation/divisional with Box 14 completed)
 - i. ☐ Deletion of Inventor(s): Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).
4. ☐ Small Entity Statement
 - a. ☐ Newly executed (original or copy)
 - i. ☐ For an independent inventor
 - ii. ☐ For a small business concern
 - iii. ☐ For a non-profit organization
 - b. ☐ Copy from a prior application (for continuation/divisional with Box 14 completed)
5. ☐ Assignment with cover sheet
6. ☐ Information Disclosure Statement (IDS)
 - a. ☐ PTO-1449
 - b. ☐ Copies of IDS citations
7. ☒ Return Receipt Postcard
8. ☐ Fees as calculated below: ☐ Check in the amount of \$_____

Address To:

Assistant Commissioner for Patents
Box Patent Application
Washington, D.C. 20231

☒ This application is filed Missing Parts

			SMALL ENTITY		NON- SMALL ENTITY	
FOR	NO. FILED	NO. EXTRA	RATE	FEE	RATE	FEE
BASIC FEE				\$345		\$690
TOT. CLAIMS	-20 =		x 9 =	\$	x 18 =	\$
IND. CLAIMS	-03 =		x 39 =	\$	x 78 =	\$
MULTIPLE DEPENDENT CLAIMS PRESENTED			\$130		\$260	
ASSIGNMENT FILING FEE			\$40		\$40	
			TOTAL		TOTAL	

UTILITY PATENT APPLICATION TRANSMITTAL <small>(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))</small>	Attorney Docket No.		1135.ACT2.PT
	First Inventor or Application Identifier		Sovine
	Title	CLEARING TRAP	
	Express Mail Label No.		EL593619398US

jc895 U.S. PTD
09/650843
08/28/00

9. ☐ Preliminary Amendment
10. ☐ English Translation Document *(if applicable)*
11. ☐ Certified Copy of Priority Document(s)
12. ☐ Microfiche Computer Program *(Appendix)*
13. ☐ Nucleotide and/or Amino Acid Sequence Submission *(if applicable, all necessary)*
- a. ☐ Computer Readable Copy
- b. ☐ Paper Copy (identical to computer copy)
- c. ☐ Statement verifying identify of above copies

14. **If a CONTINUING APPLICATION**, check appropriate box, and supply the requisite information below and in a preliminary amendment:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP)

Prior application information:

Serial No.: _____ Filing Date: _____
 Examiner: _____ Group/Art Unit: _____

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

15. Other items enclosed:

16. List of inventors/applicants:

Inventor H. Addison Sovine Citizenship USA
 Address P.O. Box 636, Provo, Utah 84603-0636

Inventor _____ Citizenship _____
 Address _____

Inventor _____ Citizenship _____
 Address _____

UTILITY PATENT APPLICATION TRANSMITTAL <small>(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))</small>	Attorney Docket No.		1135.ACT2.PT
	First Inventor or Application Identifier		Sovine
	Title	CLEARING TRAP	
	Express Mail Label No.		EL593619398US

17. CORRESPONDENCE ADDRESS

Name Randall B. Bateman
MORRISS, BATEMAN, O'BRYANT &
COMPAGNI


Registration No. 37,774

Address 5882 South 900 East, Suite 300

City Salt Lake City State Utah Zip 84121 Country Salt Lake

Telephone (801) 685-2302 Facsimile (801) 685-2303

Signature



Date

8-28-00

CERTIFICATE OF DEPOSIT UNDER 37 C.F.R. § 1.10

I hereby certify that the items listed above in this transmittal sheet are being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10 on the date indicated below and is addressed to: Assistant Commissioner for Patents, Box Patent Application, Washington, D.C. 20231.

Name: RANDALL B. BATEMAN

Date

8-28-00

Express Mail No.: EL 593619398 US

EXPRESS MAIL

ATTORNEY DOCKET NO. 1135.ACT2.PT

5

CLEARING TRAP

10

TO THE COMMISSIONER OF PATENTS AND TRADEMARKS:

15

Your petitioner, H. Addison Sovine, a citizen of the United States and resident of Utah, having a post office address at P.O. Box 636, Provo, Utah 84603-0636, prays that letters patent may be granted to him as inventor of the improvement in a Clearing Trap as set forth in the following

20

specification.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a method of decelerating projectiles. More specifically, the present invention relates to an improved clearing trap for decelerating projectiles discharged when performing a clearing check to ensure that the gun is empty.

2. State of the Art

In order to maintain proficiency in the use of firearms, it is common for law enforcement officers and sportsmen to engage in target practice. Participants will typically shoot at targets which are placed before some type of bullet containment system. After passing through the target, the bullet is typically contained in a trap where the bullet may be retrieved and recycled. Such traps include total containment system wherein the bullet is received in a chamber, and less expensive berm traps in which the bullet is received by a bullet deceleration medium.

After a target shooter is finished, it is usually a requirement that he unload the weapon for transportation and/or storage. While it is easy to remove a magazine or other container holding the bullets, it is often difficult to

accurately determine if a bullet is contained in the chamber of the gun. Numerous people have been killed or injured when a gun which was believed to be empty discharged.

To prevent such accidents from occurring, it is common for the target shooter to use a clearing trap. A clearing trap is typically a small trap disposed near the main target range into which a gun is inserted and the trigger pulled. If the gun has been properly emptied, there will be no discharge and the user will be assured that the gun is empty. However, occasionally the gun will fire due to a round that was not properly removed from the chamber. Once the round is discharged, the user may pull the trigger again for assurance that the gun is empty. Once it is demonstrated that the gun is empty, the user may store or transport the gun.

While clearing traps are important to prevent accidental discharges, the presently available traps have several disadvantages. For example, in FIG. 1A there is shown a perspective view of a prior art clearing trap, generally indicated at 10. The clearing trap 10 has a cylindrical housing 14 which has a closed lower end 18 and an upper end 22 partially enclosed by a disk with an opening for receiving the barrel of a gun. The cylindrical housing is held at an angle of between about 45 and 70 degrees so that the user may hold

the gun in a comfortable position while pulling the trigger.

The cylindrical housing 14 is filled with sand to decelerate rounds which are fired therein. When the housing 14 is sufficiently full of bullets, the housing is turned upside down and the contents removed.

The configuration shown has several disadvantages. For example, the housing 14 must be made either of specially formed steel plate (i.e. steel having a thickness of 0.25 inches), or of standard steel. Forming the steel plate into the cylindrical housing 14 is expensive, and using standard steel raises the risk that the housing will become damaged if a user fires the gun at an angle significantly tangential to the long axis of the housing.

Additionally, cleaning the housing 14 is difficult as the housing must be inverted and the sand and bullets removed. The sand in the housing is heavy, thereby requiring significant strength to lift and invert the housing 14. Also, while the housing 14 is being cleaned, the trap 10 remains out of service.

In FIG. 1B, there is shown a side cross-sectional view of an alternate type of clearing trap, generally indicated at 30. The trap 30 uses a circular containment chamber 34 similar to that disclosed in U.S. Patent Nos. 5,070,763; 5,113,700;

5,121,671; and 5,486,008. As the bullet moves through from the opening 38 through the circular containment chamber 34, the bullet is forced to travel in a circular pattern. While such movement is highly effective at decelerating the bullet, it also tends to cause lead dust to be released into the air. Additionally, the trap 30 is relatively expensive to make, as plate steel must be formed into the circular pattern and be disposed in a relatively large housing.

FIG. 1C shows yet another trap, generally indicated at 50, which is used for clearing weapons. The trap has a housing 54 with an opening 58 for inserting a gun. Disposed within the housing 54 are a plurality of rubber sheets 60. As the bullet travels through the rubber sheets 60, the bullet is decelerated until it comes to a rest.

While the sheets are effective at stopping the bullet and preventing fragmentation, they also become riddled with holes due to the bullets and begin to fall apart. If used frequently, replacement of the sheets can be relatively expensive.

Thus, there is a need for an improved clearing trap and method for bullet deceleration which provides all of the advantages of prior art clearing traps without the disadvantages of the currently available systems. Such a

system should be inexpensive, easy to use, and ensure proper deceleration of bullets which are fired into the trap.

SUMMARY OF THE INVENTION

5 Thus, it is an object of the present invention to provide a clearing trap which is less expensive than those of the prior art.

 It is another object of the present invention to provide such a clearing trap which safety decelerates bullets.

10 It is still yet another object of the present invention to provide such a clearing trap which is easy to maintain, and has minimal downtime.

 The above and other objects of the invention are realized in specific illustrated embodiments of a clearing trap having
15 a housing, a bullet deceleration insert, and a bullet decelerating material disposed within the insert for decelerating bullets fired into the trap.

 In accordance with one aspect of the invention, the housing is formed of a conventional grade steel which is
20 preformed in a desired shape (typically of square cross-section). The insert is formed of a plate steel which is sufficiently thick to stop high-power or other predetermined strength rounds. The insert may be slid into the housing for

use, and then slid out of the housing when the insert becomes sufficiently full to require emptying. While the insert is being cleaned, another insert can be placed into the housing so that there is virtually no downtime for the clearing trap.

5 In accordance with another aspect of the invention, the insert is formed from interlocking pieces of plate steel. To empty the insert, one piece must simply be moved relative to another, thereby exposing the contents of the insert and allowing for rapid cleaning and refilling of the insert.

10 In accordance with still yet another aspect of the invention, the insert is provided with a plurality of vent holes. The vent holes are configured to allow release of a small amount of air from the insert when a gun is fired into the insert - thereby dissipating the energy associated with
15 firing the gun.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other objects, features and advantages of the invention will become apparent from a consideration of the
20 following detailed description presented in connection with the accompanying drawings in which:

FIG. 1A shows a side view of a clearing trap made in accordance with the teachings of the prior art;

FIG. 1B shows a side cross-sectional view of another clearing trap made in accordance with the teachings of the prior art;

FIG. 1C shows a side cross-sectional view of another clearing trap made in accordance with the teachings of the prior art;

FIG. 2 shows a side view of a clearing trap made in accordance with the principles of the present invention, and a gun inserted into the clearing trap;

FIG. 3 shows a side cross-sectional view of the clearing trap shown in FIG. 2;

FIG. 4 shows a disassembled top view of a bullet deceleration insert for use in the clearing trap shown in FIGs. 2 and 3; and

FIG. 5A shows a plan view of a pair of end plates disposed at the end of an insert made in accordance with principles of the present invention;

FIG. 5B shows a fragmented side view of the housing, with the orientation of the end plates demonstrated in shadow; and

FIG. 6 shows an end view of the bottom wall and sidewalls of an insert with a different end plate configuration attached thereto.

DETAILED DESCRIPTION

Reference will now be made to the drawings in which the various elements of the present invention will be given numeral designations and in which the invention will be discussed so as to enable one skilled in the art to make and use the invention. It is to be understood that the following description is only exemplary of the principles of the present invention, and should not be viewed as narrowing the pending claims.

FIG. 2 shows a side view of a clearing trap, generally indicated at 100, made in accordance with the principles of the present invention. The clearing trap 100 includes an elongate housing 104 into which a gun 108 is inserted and the trigger pulled in order to ensure that the gun has been properly unloaded. The housing 104 is typically formed by an outer wall surrounding a void.

A pair of flanges 112 and 114 are positioned adjacent the top of the housing 104. The flanges 112 and 114 extend outwardly 104 and hold a rubber shield 116 to form a face plate with an opening for receiving the gun 108. As will be explained in additional detail below, the flanges 112 and 114 can be attached directly to the housing 104 or to an insert (not shown) which nests within the housing.

The housing 104 is preferably made of a tube of conventional steel having a square cross-section. The housing 104 is disposed at an angle of between about 50 and 70 to the horizontal so that the user may maintain a comfortable position when performing the clearing check on the gun 108.

The housing 104 is supported by a leg 120 which prevents the housing from being accidentally pulled toward the user. A base plate 124 is attached to the bottom the housing 104 and the leg 120 to provide lateral stability. For reasons which are discussed in additional detail below, the base plate 124 can be anchored to the floor by bolts or some other securement mechanism if desired.

Turning now to FIG 3, there is shown a cross-sectional view of the housing 104 of FIG. 2. A bullet deceleration insert 130 is disposed in the housing 104 and extends substantially the length thereof. The bullet deceleration insert 130 is preferably slidably removable from the housing 104 by pulling the insert upwardly along the long axis of the housing. While the housing 104 is typically made of steel, it can also be made of other materials, such as plastic, wood, etc. The housing 104 may be made from materials other than those conventionally used for bullet deceleration because the insert 130 is made from steel which is sufficiently hard and

thick (i.e 0.25 inch plate steel) to withstand a desired round. Because the insert 130 decelerates the bullet, the housing 104 does not have to withstand a significant amount of force.

5 As shown in FIG. 3, the insert 130 is filled with a bullet deceleration medium 134, such a chopped pieces of rubber, which preferably decelerates the bullet before it reaches the lower end 130a of the insert. At the opposing upper end 130b, the insert 130 may be attached to the flanges 10 112 and 114 and rubber shield 116 forming the face plate so that the flanges 112 and 114 form a stop which limits advancement of the insert into the housing 104. In the alternative, the housing 104 can simply be sized so that the insert 130 can only be advanced a predetermined distance into 15 the housing 104 before being stopped by the base plate 124 or some other obstruction.

While not shown in FIG. 3, the insert may also include a plurality of vents. The vents allow the force produced by firing a round at close range to be more readily dissipated. 20 If any deceleration medium 134 escapes from the insert 130 through the vents, it will simply collect at the bottom of the housing 104 and may be cleaned out at a later time by use of a vacuum, shovel, etc.

Also discussed in detail below with respect to a preferred embodiment of the insert 130 is that one wall of the insert can be removed from the remaining portions to facilitate rapid cleaning of the insert. When such a configuration is used, the removable wall is disposed adjacent the upper sloping sidewall 104a of the housing 104. In such a configuration, the upper wall of the insert 130 is unlikely to accidentally open under the weight of the bullet deceleration medium 134 and bullets contained therein.

Turning now to FIG. 4, there is shown a partially disassembled top view of the insert 130. The insert 130 is preferably formed by a bottom portion 138 comprising a bottom wall 140 and a pair of sidewalls 144 attached to the bottom wall so as to form a U-shaped cross-section. Ideally, the sidewalls 144 are connected to the bottom wall 140 by a plurality of interlocking channels 146 and tabs 148. The bottom wall 140 is then welded to the sidewalls 144 to form a three sided container. An end plate 152 is disposed on the lower end 130a of the insert 130 and is preferably welded to the bottom wall 140 and the sidewalls 144. The end plate 152 can be formed from a solid piece of plate or, as is explained below, may be formed from overlapping plates with slots which provide vents for the insert 130.

Also shown in FIG. 4 is the top wall 156. Unlike the bottom wall 140 and the sidewalls 144, the top wall 156 is not welded to the remaining portions of the insert 130. Rather, the top wall 156 has tabs 160 and channels 164 which engage the channels 146 and tabs 148 of the sidewalls 144 to facilitate attachment to the bottom portion 138. Preferably, the tabs and channels 146, 148, 160 and 164 engage one another to leave a plurality of small vents along the insert 130. The vents allow a small amount of air to escape the insert 130 to dissipate the force associated with firing a gun into the insert, but are sufficiently small that a bullet could not pass therethrough without obliterating the bullet.

The insert 130 embodiment shown in FIG. 4 is a presently preferred embodiment because, by having the top 156 readily removable from the sidewalls 144, the insert 130 can be opened and cleaned with very little effort. Once returned to its place, however, the top 156 securely engages the sidewalls 144 and the insert 130 forms a highly effective bullet trap. While providing less efficient cleaning, the insert could be formed with all four plates fixedly attached to each other to form a tubular insert closed at the bottom by the end plate 152.

One principle advantage of the configuration of the

present invention is that it is generally of lower cost than the prior art. Because the housing 104 does not need to be extremely bullet resistant, off-the-shelf square tubing can be used. While the steel plate necessary to make the insert 130 is generally expensive, the relatively small sizes which are used for the bottom 140, sidewalls 144 and top 156 are readily obtainable from scrap left over from cutting larger pieces of plate for full sized bullet containment traps. Thus, the primary costs associated with the clearing trap 100 are the labor to cut the pieces and weld them together.

Turning now to FIGs. 5A, there is shown a bottom view an end plate 152' made in accordance with principles of the present invention. While the lower end 130a of the insert 130 can be formed by a solid end plate 152 as discussed above, it is preferably formed by a pair of plates. A first plate 152A (which is shown in shadow in FIG. 5A) is configured with three slots 170 therein. A second plate 152B is configured with four slots 174 therein. As shown in FIG. 5A, when the first and second plates 152A and 152B are oriented so that the slots 170 and 174 are parallel, the slots do not overlap. Thus, there is no straight line which a projectile could follow and pass through both the slots 170 in the first plate 152A and the slots 174 in the second plate 152B.

FIG. 5B shows a side view of the housing 104 with the insert 130, including the end plate 152' shown in shadow. Preferably, the first plate 152A and the second plate 152B are also spaced apart slightly when they are welded to the bottom 140 and sidewalls 144. This spacing allows airflow to pass through the slots 170 and 174 while substantially eliminating the probability of a bullet passing through slots. Of course, the narrower the slots 170 and 174, the less the likelihood that a bullet would pass therethrough. Furthermore, it is important to remember that very few bullets will ever reach the end plate 152' due to the bullet deceleration medium 134 (FIG. 3) disposed in the insert.

While the configuration shown in FIG. 5A and 5B is a preferably preferred embodiment, the first and second plates 152A and 152B could be rotated so that the slots 170 and 174 overlap one another, thereby leaving small holes in the bottom plate 152 to allow air flow, yet substantially prevent bullet fragments from passing therethrough.

FIG. 6 shows an end view of the bottom wall 140' and sidewalls 144' of an insert 130'. Unlike the insert discussed above, the bottom wall 140', the sidewalls 144', and the top wall 156' are simply welded together. While such a configuration does not provide vents, vents could be provided

if desired by either forming grooves into the edges of the bottom wall 140', sidewalls 144' or top wall 156', or by drilling holes in the walls.

5 Disposed at the far end of the insert 130' is a single end plate 152''. The end plate 152'' has six small slots 170' formed therein to provide venting of the insert. By providing vents, the force of generated by discharging the gun is dissipated and the risk of the force blowing bullet deceleration medium 134 (FIG. 3) back at the user is
10 minimized.

Thus there is disclosed an improved clearing trap for use with firearms which is inexpensive, easy to construct and to use. While the embodiment shown in FIGs. 2 through 6 are currently preferred embodiments, those skilled in the art will
15 appreciate that numerous modifications can still be made within the principles of the present invention. For example, while a square cross-section is presently preferred for the housing 104 and the insert 130 or 130' because plate pieces of steel plate are readily available, the housing and the insert
20 could be formed with some other cross-sectional geometry. Likewise, those skilled in the art will appreciate that numerous other modifications could be made to the invention with respect to the vents or other aspects of the housing 104

or inserts 130 and 130'. The appended claims are intended to cover such modifications.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2

CLAIMS

1. A trap for receiving bullets, the trap comprising:
a housing having a cavity defined by an outerwall
surrounding a void; and

5 an insert forming a bullet deceleration chamber, the
insert being slidably insertable into and removable from the
void of the housing.

2. The trap for receiving bullets according to claim 1,
10 wherein the insert is formed by a plurality of pieces of steel
plate.

3. The trap for receiving bullets according to claim 2,
wherein the plurality of pieces of steel plate form a bottom
15 portion having a generally u-shaped cross-section and a top
removably engaging the bottom portion such that the insert has
a square cross-section when the top is attached.

4. The trap for receiving bullets according to claim 3,
20 wherein the bottom portion is formed by a bottom and a pair of
sidewalls, the bottom and sidewalls being fixedly attached to
one another.

5. The trap for receiving bullets according to claim 1, wherein the insert comprises a plurality of vents for releasing force from the insert when a gun is fired into the insert.

5

6. The trap for receiving bullets according to claim 5, wherein the insert is formed from a top plate, a bottom plate and a pair of sidewalls, and wherein the vents are formed between the sidewalls and at least one of the top plate and the bottom plate.

10

7. The trap for receiving bullets according to claim 5, wherein the insert has at least one plate forming a lower end, and wherein the at least one plate has at least one slot formed therein.

15

8. The trap for receiving bullets according to claim 7, wherein the insert has two bottom plates and wherein the bottom plates each have slots formed therein.

20

9. The trap for receiving bullets according to claim 8, wherein the plates are aligned such that the slots in the plates do not overlap.

10. The trap for receiving bullets according to claim 1, wherein the insert further comprises a bullet deceleration medium disposed therein.

5 11. The trap for receiving bullets according to claim 10, wherein the bullet deceleration medium is formed by pieces of rubber.

10 12. The trap for receiving bullets according to claim 1, wherein the housing is formed from a tube having a generally square cross-section.

15 13. The trap for receiving bullets according to claim 1, wherein the housing is formed from a material other than plate steel.

14. A clearing trap for receiving bullets fired from a gun, the clearing trap comprising:

20 a housing having an outerwall and a void disposed within the outerwall; and

 an insert disposed in the void of the housing, the insert forming a bullet deceleration chamber and having at least one vent formed therein.

15. The clearing trap according to claim 14, wherein the insert is slidably removable from the housing.

16. The clearing trap according to claim 14, wherein the insert is formed by a bottom portion and a top portion, the top portion being removable from the bottom portion.

17. The clearing trap according to claim 14, wherein the insert is filled with a removable bullet deceleration medium.

18. The clearing trap according to claim 14, further comprising a leg attached to the housing for supporting the housing.

19. The clearing trap according to claim 18, further comprising a base plate attached to the housing and the leg.

20. A method for forming a clearing trap, the method comprising;

selecting a housing having a void configured to receive a bullet deceleration chamber;

selecting a bullet deceleration chamber; and

sliding the bullet deceleration chamber into the void

configured to receive the bullet configuration.

21. The method according to claim 20, wherein the method
former comprises forming a face plate at one end of the
housing or insert.

22. The method according to claim 20, wherein the method
further comprises filling the bullet deceleration chamber with
a bullet deceleration medium.

23. The method according to claim 20, wherein the method
comprises, forming the bullet deceleration chamber from a
plurality of generally flat pieces of steel.

24. The method according to claim 23, further comprising
fixedly attaching a plurality of the generally flat pieces of
steel, and releasably attaching at least one of the generally
flat pieces of steel to the plurality of generally flat pieces
of steel which are fixedly attached.

25. The method according to claim 20, wherein the method
comprises forming a plurality of vents in the bullet
deceleration chamber.

ABSTRACT OF THE DISCLOSURE

A clearing trap for decelerating bullets includes a housing and a bullet decelerating insert disposed within the housing. Preferably, the insert is slidably removable from the housing and is provided with a plurality of vents which help dissipate the force associated with firing a gun into a small enclosure. Also preferably, a portion of the insert is detachable or openable to facilitate periodic cleaning of the insert.

Fig. 1 is a perspective view of a cylindrical member 10. The member has a longitudinal slot 14 extending along its length. At one end of the member, there is a circular opening 22. A vertical line 18 is shown adjacent to the slot, possibly indicating a cross-section or a specific feature.

FILE 1B
(Prior Art)

FIG. 1C
(Prior Art)




FIG. 2




Fig. 3





FIG. 4



03230" E+203360

FIG. 5A




FIG. 5B




FIG. 6

